



	Project Cable Band Bolt - Factor of Safety			File location BC04_Cable_Bands Calc sheet no. <u>rev</u>	
	Drawing Ref 33111/AB/20	Calc by DB	Date Jul2011	Chk by	Date
Ref	Calculations			Output	
	<u>Determine FOS of Cable Band Bolt</u> The cable band bolts on the FRB were replaced between 2000 and 2001. Since the installation of the cable band bolts several defects have been found with the new system which has resulted in concerns in regards to the FOS to prevent slipping of the cable bands. The following defects have been noted: 1, Several cable band nuts have cracked and thus failed releasing the tensile load within the bolt. 2, The actual load achieved during tensioning of the bolt group was less than specified. The tension within the bolts prevents slipping of the cable bands through friction, therefore any loss of tension will result in a reduction in the FOS. These calcs determine the achieved FOS. There are 3 arrangement of cable band bolts, drawings and details can be found in the following file: G:\DRAWINGS\BC 16 suspenders\Replacement of Hangers Drawing No: 33111/AB/20 Arrangement details given below for reference:  CABLE BAND # 1 24 No. AS SHOWN CABLE BAND # 2 40 No. AS SHOWN CABLE BAND # 3 128 No. AS SHOWN Specifications details of the cable bands can be found here: G:\filing\BC FILES\BC04 Cable Bands\Original Bolt Spec				

		Project Cable Band Bolt - Factor of Safety			File location BC04_Cable_Bands	
		Drawing Ref 33111/AB/20			Calc sheet no	rev
		Calc b	Date	Chk by	Date	
		DB	Jul2011			
Ref	Calculations				Output	
	<u>Determine FOS of Cable Band Bolt</u> Calculate the angle of applied load Angle of load transvered to cable band varies throughout its length. From Report on loading a survey of the cable was undertaken in 1986 and can be found in the FRB 'blue book' Vol vi verification part F. From the survey information a graph was plotted to determine the equation of the main cable line and has been determined as follows: Main Span Equation: $f(x) = 0.000358x^2 - 0.3556x + 154.13$ (see attached graph for verification) Side Span South Equation: $f(x) = 0.0.000493x^2 + 0.0865x + 50.075$ (see attached graph for verification) Side Span North Equation: $f(x) = 0.0.000501x^2 - 0.4626x + 153.64$ (see attached graph for verification) These second order polynominal equations are used to calculate the slope at any given Panel Point Number. Example - Determine slope at first hanger south Main Span: $f'(x) = 0.00072 x - 0.3556$ $f'(18.288) = -0.34208 \quad x = 18.882 \text{ PP 48S}$ $f'(182.88) = 0.34187 \quad x = 974.118 \text{ PP 66N}$ Side Span South $f'(x) = 0.00099 x + 0.0865$ $f'(18.882) = 0.44122 \quad x = 359.758 \text{ PP 42S}$ Side Span North $f'(x) = 0.00099 x - 0.4601$ $f'(18.882) = -0.44148 \quad x = 18.882 \text{ PP 42S}$				Equ 1 Equ 2 Equ 3 MS Max Slope SS S Max Slope 0.4412 SS NMax Slope	

		Project			File location		
		Cable Band Bolt - Factor of Safety			BC04_Cable_Bands		
					Calc sheet no.	rev	
Ref		Drawing Ref	Calc by	Date	Chk by	Date	
		33111/AB/20	DB	Jul2011			
		Calculations				Output	
		<u>Determine the live load applied to Hanger</u> In accordance with the FRB ICE proceedings section 2.113 the hangers were designed to accommodate the following loads: <u>Main Span Design Loads</u> Combination 1 - KEL, UDL 657ft loaded length Dead Load = 113 tons Live Load = 45 tons Total = 1550 kN <u>Side Span Design Loads</u> Combination 1 - KEL, UDL 657ft loaded length Dead Load = 167 tons Live Load = 50 tons Total = 2128.8 kN <u>BSALL Loading</u> Note that hanger loads used by MB were less than original live loads; 380kN used opposed to 490.5kN Side Span and 442kN Main Span. Calculations undertaken by MB stated that Hanger tensions were calculated from PP32 and extrapolated to others. However in November 2008 W.A.Fairhurst & Partners determined the hanger loads at each panel point. Appendix B attached for Ref. Using these hanger loads it can be seen that for both the side span and the main span the factor of safety can be seen to drop slightly as shown in summary table 3. It can be seen that the increase in dead load of the structure presumably from an increase in superimposed dead loads is the largest contributor to the increase in load. <u>Determine Slip Force</u> F_h = Load from Hanger F_s = Force which causes sliding $F_s = F_h \cos \theta$  PP 48S Example Slope = 0.342 $\therefore \theta = \tan^{-1}(1/0.342) = 71.1152^\circ$ Assume $F_h = 1550$ $\therefore F_s = 1550 * \cos 71.115 = 501.68$ kN					
						PP 48S $F_s = 502$ kN	

	<u>Project</u> Cable Band Bolt - Factor of Safety			<u>File location</u> BC04_Cable_Bands	
	<u>Drawing Ref</u> 33111/AB/20		<u>Calc by</u> DB	<u>Date</u> Jul2011	
				<u>Calc sheet no</u>	<u>rev</u>
Ref	Calculations				Output
	<u>Determine the Slip Factor/Coefficient of Friction</u> The slip factor will have a direct and very significant impact on the capacity of the cable band to resist sliding forces. The friction capacity of the cable band is given by: $P_D = F_v \cdot \mu \cdot N$ Where: P_D = Friction Capacity (kN) F_v = Prestress Load of cable band bolt (kN) μ = Slip factor N = No. of bolts Unfortunately no tests were carried out during construction to determine the friction between cable band bolts and main cables. From the FRB ICE proceedings friction between the wires of the main cable and metal sprayed surfaces of the saddles was assumed to be equal to 15%. The Proceedings state that practical test made by the Contractor gave results of 30% however no details of these are provided. Results from these tests would suggest that slip factor up to 30% could be justified. Testing has been carried out for other suspension bridges for example for the Delaware River Bridge full size test was carried out by Lehigh University. The conclusion of these test were that bulging of the main cable contributed significantly to resisting slip. It can be seen however that during the test the replica of the main cable was not under any force. Insitu however the main cable will be under considerable tensile force which will prevent the majority of bulging that was experienced during the test. Therefore it is assumed that there is no additional friction as a result of bulging. Tests of individual galvanised wires also carried out by Lehigh University show that for a smooth surface an average of 20.4% slip factor was achieved. Rougher surfaces of galvanised wire resulted in a reduction in friction. A "rough surface, 17 cuts per inch" achieved a slip factor of only 16.9%. BS 5400 part 3 clause 14.5.4.4 gives slip factors at friction surfaces for HSFG bolts. For surfaces with sprayed zinc $\mu = 0.40$ has been specified.				

	Project Cable Band Bolt - Factor of Safety			File location BC04_Cable_Bands													
				Calc sheet no.	rev												
	Drawing Ref 33111/AB/20	Calc by DB	Date Jul2011	Chk by	Date												
Ref	Calculations				Output												
	<u>Determine the Slip Factor/Coefficient of Friction (cont)</u> Neither BS 5400 or the Eurocodes provide a slip factor for galvanised surfaces. Various tests have been carried out for galvanised surface and results range significantly. The Galvanisers Association specifies the following slip factors are achieved depending on the preparation of the surface: <table border="0"> <thead> <tr> <th>Preparation Technique</th> <th>μ</th> </tr> </thead> <tbody> <tr> <td>As galvanised</td> <td>0.14</td> </tr> <tr> <td>Weathered galvanised</td> <td>0.20</td> </tr> <tr> <td>Galvanised-wire brush</td> <td>0.31</td> </tr> <tr> <td>Galvanised-grit blasted</td> <td>0.31</td> </tr> <tr> <td>Bare steel, as-rolled</td> <td>0.35</td> </tr> </tbody> </table> Galvanised surfaces slip factor range quite significantly depending on the surface preparation however as the section were galvanised during construction during in the 1960's the surface preparation could be described as weathered. This would confirm the results from the Delaware river bridge of 20.4%. Some time after the connection is made the Galvanisers Association states that galvanised joints will develop a characteristic known as 'lock-up' The 'lock-up' is a result of friction between the two galvanized surfaces during dynamic movements. After 'lock up' a friction coefficient equal to that of bare steel can be achieved as above (35%). It is assumed for these calculations that no dynamic movement can occur at the connection interface during construction as this would result in failure of the joint and therefore 'lock up' of the joint is not achieved. Assumed Slip Factor For these calculations a slip factor $\mu = 0.200$ Determine Capacity of Connection to Resist Slip $P_D = F_v \cdot \mu \cdot N$ Example PP 48S $F_v = 800 \text{ kN}$ (assumed, see later section for actual prestress force) $N = 6 \text{ No.}$ $P_D = 800 \times 0.200 \times 6 = 960 \text{ kN}$				Preparation Technique	μ	As galvanised	0.14	Weathered galvanised	0.20	Galvanised-wire brush	0.31	Galvanised-grit blasted	0.31	Bare steel, as-rolled	0.35	$\mu = 0.200$ $P_D = 960 \text{ kN}$
Preparation Technique	μ																
As galvanised	0.14																
Weathered galvanised	0.20																
Galvanised-wire brush	0.31																
Galvanised-grit blasted	0.31																
Bare steel, as-rolled	0.35																

		Project			File location	
		Cable Band Bolt - Factor of Safety			BC04_Cable_Bands	
					Calc sheet no.	rev
		Drawing Ref	Calc by	Date	Chk by	Date
		33111/AB/20	DB	Jul2011		
Ref	Calculations					Output
BS 5400 Part 1 Table 1 As per WAF Hanger load App B BS5400 Table 2 CI 14.5.4.2 As per WAF Hanger load App B	<u>Determine the FOS against Slip</u>					FOS with $\mu = 0.20$ 1.9136
	Example PP48 S					
	FOS = $\frac{\text{Capacity to Resist Slip}}{\text{Slip Force}} = \frac{960}{501.677} =$					
	For comparison the FOS against slip with $\mu = 0.3$ is given below					
	FOS with slip of 0.3 = 2.87					
	<u>Determine the Required FOS against Slip</u>					
	Dead Load (steel) $y_{fi} = 1.05$ $y_{fi} * y_{f3} =$ $y_{FDL} = 1.05$					
	Superimposed Dead $y_{fi} = 1.2$ $y_{fi} * y_{f3} =$ $y_{FSD} = 1.2$					
	Live Load $y_{fi} = 1.5$ $y_{fi} * y_{f3} =$ $y_{FLL} = 1.5$					
	<u>Side Span</u>					
	Dead Load Percentage of total load = 66.52% $*y_{FDL} = 0.698$					
Superimposed load % of total load = 14.17% $*y_{FSD} = 0.170$						
Live load Percentage of total load = 19.31% $*y_{FLL} = 0.290$						
Σ 100.00% $y_F = 1.158$						
In accordance with BS 5400 Part-3 the Partial Factor of safety applied to the friction capacity of HSFG is:						
$y_{f3} = 1.1$						
$y_{m1} =$ Is partial factor for characteristic yield stress						
$y_{m2} =$ Is partial factor for modelling uncertainties						
$y_m = y_{m1} * y_{m2} = 1.3$ Friction capacity of HSFG						
This partial factor of safety is assumed appropriate to prevent slip of the cable band bolts.						
Side Span required FOS must be $> y_F * y_m * y_{F3} =$ 1.6561						
Note that current practices for the design of a suspension bridge cable will adopt a material factor of 1.67 for tension in the cable.						
Recalculating the FOS required for using 1.67 = $1.67 * y_F =$ 2.1275						
<u>Main Span</u>						
Dead Load Percentage of total load = 56.93% $*y_{DL} = 0.598$						
Superimposed load % of total load = 17.81% $*y_{SD} = 0.214$						
Live load Percentage of total load = 25.26% $*y_{LL} = 0.379$						
Σ 100.00% 1.190						
Main Span required FOS must be $> y_m * y_F =$ 1.7023						
Recalculating the FOS required for using 1.67 = $1.67 * y_F =$ 2.1868						
<u>Conclusion</u>						
If FOS using $\mu = 0.20 > y_m * y_F$ then capacity is sufficient						
Therefore capacity is sufficient if y_m of 1.3 is used but insufficient if material factor is taken as 1.67						

	<u>Project</u> Cable Band Bolt - Factor of Safety			<u>File location</u> BC04_Cable_Bands	
				<u>Calc sheet no.</u>	<u>rev</u>
	<u>Drawing Ref</u> 33111/AB/20	<u>Calc by</u> DB	<u>Date</u> Jul2011	<u>Chk by</u>	<u>Date</u>
Ref	Calculations				Output
	<u>Determine Tensile Force in Cable Band Bolts</u> $E = \sigma / \epsilon \quad \epsilon = \text{Strain} = \Delta L / L$ $\sigma = \text{Stress} = F_v / A$ $E = \text{Youngs Modulus}$ $F_v = E \cdot A \cdot (\Delta L / L) - \text{Relaxation of Stress}$ Original specified force was 800kN. Measurements taken during installation resulted in a force between 770kN and 800kN. Extensions of bolts were re-measured by FRB in 2007 and 2008. Results showed a decrease in the amount of force within cable band bolts. The reduced force within the cable band has been used to calculate the Factor of safety at each hanger location.				

		Project				File location		
		Cable Band Bolt - Factor of Safety				BC04_Cable_Bands		
						Calc sheet no.	rev	
Drawing Ref		Calc by		Date		Chk by	Date	
33111/AB/20		DB		Jul2011				
Ref	Calculations						Output	
Determine Factor of Safety against slip μ = 0.3								
Table 1 - Input Values as MB Calcs								
	Panel Point	Angle Radians	No Bolts	Bolt Tension (kN)	Dead Load, nom (kN)	Live Load, nom (kN)	Total Load, nom (kN)	FoS
Side Span ↑	2	0.0865	4	800	1540	380	1920	5.788
	4	0.1061	4	800	1540	380	1920	4.721
	6	0.1236	4	800	1540	380	1920	4.056
	8	0.1411	4	800	1540	380	1920	3.555
	10	0.1580	4	800	1540	380	1920	3.178
	12	0.1762	4	800	1540	380	1920	2.852
	14	0.1938	4	800	1540	380	1920	2.596
	16	0.2113	4	800	1540	380	1920	2.384
	18	0.2289	6	800	1540	380	1920	3.305
	20	0.2465	6	800	1540	380	1920	3.074
	22	0.2641	6	800	1540	380	1920	2.873
	24	0.2817	6	800	1540	380	1920	2.698
	26	0.2994	6	800	1540	380	1920	2.543
	28	0.3170	6	800	1540	380	1920	2.406
	30	0.3347	6	800	1540	380	1920	2.283
	Main Span ↑	32	0.3524	8	800	1540	380	1920
34		0.3701	8	800	1540	380	1920	2.765
36		0.3878	8	800	1540	380	1920	2.644
38		0.4056	8	800	1540	380	1920	2.534
40		0.4233	8	800	1540	380	1920	2.434
42		0.4432	8	800	1540	380	1920	2.332
44		N/A	N/A	N/A	N/A	N/A	N/A	N/A
46		N/A	N/A	N/A	N/A	N/A	N/A	N/A
46		0.3473	6	800	1050	380	1430	2.959
48		0.3326	6	800	1050	380	1430	3.084
50		0.3194	6	800	1050	380	1430	3.207
52		0.3063	4	800	1050	380	1430	2.226
54		0.2932	4	800	1050	380	1430	2.323
56		0.2800	4	800	1050	380	1430	2.429
58		0.2669	4	800	1050	380	1430	2.545
60		0.2538	4	800	1050	380	1430	2.674
62	0.2408	4	800	1050	380	1430	2.815	
64	0.2277	4	800	1050	380	1430	2.974	
66	0.2146	4	800	1050	380	1430	3.152	
68	0.2016	4	800	1050	380	1430	3.353	
70	0.1885	4	800	1050	380	1430	3.583	
72	0.1755	4	800	1050	380	1430	3.845	
74	0.1625	4	800	1050	380	1430	4.149	
76	0.1494	4	800	1050	380	1430	4.510	
78	0.1364	4	800	1050	380	1430	4.937	
80	0.1234	4	800	1050	380	1430	5.454	
82	0.1104	4	800	1050	380	1430	6.093	
84	0.0974	4	800	1050	380	1430	6.903	
86	0.0844	4	800	1050	380	1430	7.964	
88	0.0714	4	800	1050	380	1430	9.410	
90	0.0584	4	800	1050	380	1430	11.502	
92	0.0454	4	800	1050	380	1430	14.792	
94	0.0325	4	800	1050	380	1430	20.660	
96	0.0195	4	800	1050	380	1430	34.429	
98	0.0065	4	800	1050	380	1430	103.282	
1. Hanger tension calculated for PP32 and extrapolated to others 2. BSALL (175m), KEL, ftwy: 5kN/m2 2 bays, BSFLL (175m) 3. Assumes "slope" was meant to be angle in radians. Note that if you assume that the "Slope" provided by MB is an angle in radians then calculated values are exactly the same as per MB Calcs. The angle provided however is a slope and not an angle It can therefore be seen that MB calcs are incorrect. See next sheet for justification								
Side Span Minimum FOS = 2.283								
Side Span Minimum FOS = 2.226								

		Project			File location			
		Cable Band Bolt - Factor of Safety			BC04_Cable_Bands			
					Calc sheet no.		rev	
Drawing Ref		Calc by		Date	Chk by	Date		
33111/AB/20		DB		Jul2011				
Ref	Calculations						Output	
Determine Factor of Safety against slip μ = 0.3								
Table 2 - Check MB Angle Against Calculated Angle								
	Panel Point	MB Slope	Calculate Angle (°) Assume MB Slope	Calculate Angle (°) Assume MB Angel in Radians	Slope Determined From Survey	Calculate Angle (°) From Survey	% Difference if MB is Slope	% Difference if MB is Angle
Side Span	2	0.087	4.944	4.956	0.069	3.955	20.010%	20.209%
	4	0.106	6.056	6.079	0.088	5.015	17.201%	17.509%
	6	0.124	7.046	7.082	0.106	6.071	13.832%	14.267%
	8	0.141	8.031	8.084	0.125	7.124	11.298%	11.880%
	10	0.158	8.979	9.053	0.144	8.172	8.985%	9.731%
	12	0.176	9.993	10.096	0.162	9.214	7.794%	8.731%
	14	0.194	10.968	11.104	0.181	10.250	6.543%	7.687%
	16	0.211	11.931	12.107	0.199	11.280	5.459%	6.829%
	18	0.229	12.893	13.115	0.218	12.302	4.584%	6.200%
	20	0.247	13.847	14.123	0.237	13.316	3.836%	5.716%
	22	0.264	14.794	15.132	0.255	14.322	3.191%	5.352%
	24	0.282	15.733	16.140	0.274	15.319	2.629%	5.089%
	26	0.299	16.668	17.154	0.293	16.306	2.168%	4.943%
	28	0.317	17.589	18.163	0.311	17.284	1.732%	4.838%
	30	0.335	18.505	19.177	0.330	18.251	1.373%	4.826%
	32	0.352	19.412	20.191	0.348	19.208	1.053%	4.868%
	34	0.370	20.310	21.205	0.367	20.154	0.767%	4.958%
	36	0.388	21.196	22.219	0.386	21.088	0.510%	5.091%
	38	0.406	22.077	23.239	0.404	22.011	0.302%	5.285%
	40	0.423	22.943	24.253	0.423	22.922	0.092%	5.490%
	42	0.443	23.903	25.393	0.441	23.821	0.344%	6.194%
	44	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	46	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	48	0.347	19.152	19.899	0.342	18.885	1.396%	5.096%
	50	0.333	18.397	19.057	0.329	18.189	1.134%	4.555%
	52	0.319	17.713	18.300	0.315	17.487	1.281%	4.446%
	54	0.306	17.030	17.550	0.302	16.779	1.472%	4.390%
	56	0.293	16.341	16.799	0.288	16.067	1.680%	4.361%
	58	0.280	15.642	16.043	0.274	15.349	1.877%	4.327%
	60	0.267	14.944	15.292	0.261	14.626	2.128%	4.357%
Main Span	62	0.254	14.241	14.542	0.247	13.898	2.406%	4.424%
	64	0.241	13.539	13.797	0.234	13.166	2.754%	4.571%
	66	0.228	12.828	13.046	0.220	12.430	3.103%	4.727%
	68	0.215	12.112	12.296	0.207	11.689	3.494%	4.936%
	70	0.202	11.398	11.551	0.193	10.944	3.984%	5.254%
	72	0.189	10.675	10.800	0.180	10.195	4.492%	5.600%
	74	0.176	9.954	10.055	0.166	9.443	5.130%	6.087%
	76	0.163	9.230	9.311	0.153	8.688	5.871%	6.687%
	78	0.149	8.497	8.560	0.139	7.930	6.679%	7.365%
	80	0.136	7.767	7.815	0.126	7.168	7.710%	8.276%
	82	0.123	7.035	7.070	0.112	6.405	8.958%	9.416%
	84	0.110	6.300	6.325	0.099	5.638	10.499%	10.860%
	86	0.097	5.563	5.581	0.085	4.870	12.451%	12.726%
	88	0.084	4.824	4.836	0.072	4.101	15.003%	15.204%
	90	0.071	4.084	4.091	0.058	3.329	18.482%	18.620%
	92	0.058	3.342	3.346	0.045	2.557	23.506%	23.593%
	94	0.045	2.599	2.601	0.031	1.783	31.403%	31.450%
	96	0.033	1.861	1.862	0.018	1.009	45.795%	45.814%
	98	0.020	1.117	1.117	0.004	0.234	79.009%	79.012%
	100	0.007	0.372	0.372	-0.009	179.460	-48087.850%	-48087.171%
1. Hanger tension calculated for PP32 and extrapolated to others 2. BSALL (175m), KEL, ftwy: 5kN/m2 2 bays, BSFLL (175m) 3. Slope as per MB calculations As can be seen from the table the slope from MB calculations correspond well with the slope determined from survey dimension taken in 1886. Significant difference are detected if the slope is used as and angle in radians.								Much better correlation if MB column is slope rather than angle in radians.

		Project					File location		
		Cable Band Bolt - Factor of Safety					BC04_Cable_Bands		
							Calc sheet no.		rev
Drawing Ref					Calc by	Date	Chk by	Date	
33111/AB/20					DB	Jul2011			
Ref	Calculations							Output	
Side Span Main Span	Determine Factor of Safety Against Slip $\mu = 0.3$							HA Side Span Minimum FOS FOS = 2.139 BSALL Side Span Minimum FOS FOS = 2.353 HA Side Span Minimum FOS FOS = 2.065 Side Span Minimum FOS FOS = 2.342	
	Table 2 - Re-calculated with HA and BSALL As per Hanger report								
	Panel Point	Slope	No Bolts	Bolt Tension (kN)	Dead + HA Loads + Footway (BD 37/01)	HA FOS	Dead + BSALL (2006) + Footway (BD 37/01)		BSALL FoS
	2	0.0691	4	800	2560	5.438	2180		6.385
	4	0.0877	4	800	2110	5.205	1920		5.720
	6	0.1064	4	800	2160	4.202	1970		4.607
	8	0.1250	4	800	2030	3.813	1850		4.184
	10	0.1436	4	800	2090	3.231	1900		3.555
	12	0.1622	4	800	2110	2.841	1930		3.106
	14	0.1808	4	800	2150	2.509	1960		2.752
	16	0.1995	4	800	2130	2.304	1930		2.543
	18	0.2181	6	800	2140	3.158	1940		3.484
	20	0.2367	6	800	2150	2.908	1940		3.223
	22	0.2553	6	800	2140	2.720	1930		3.016
	24	0.2739	6	800	2170	2.512	1960		2.781
	26	0.2925	6	800	2170	2.363	1970		2.603
	28	0.3112	6	800	2140	2.265	1940		2.498
	30	0.3298	6	800	2150	2.139	1950		2.358
	32	0.3484	8	800	2180	2.677	1980		2.947
	34	0.3670	8	800	2120	2.629	1930		2.887
	36	0.3856	8	800	2110	2.529	1940		2.751
	38	0.4042	8	800	2130	2.405	1950		2.627
	40	0.4229	8	800	2150	2.293	1980		2.490
	42	0.4415	8	800	2170	2.191	2020		2.353
	44	N/A	N/A	N/A	N/A	N/A	N/A		N/A
	46	N/A	N/A	N/A	N/A	N/A	N/A		N/A
	48	0.3421	6	800	1370	3.247	1310		3.396
	50	0.3286	6	800	1530	3.015	1390		3.319
	52	0.3150	6	800	1590	3.014	1420		3.375
	54	0.3015	4	800	1610	2.065	1420		2.342
	56	0.2880	4	800	1660	2.090	1460		2.376
	58	0.2745	4	800	1690	2.146	1480		2.451
	60	0.2610	4	800	1680	2.263	1470		2.586
	62	0.2474	4	800	1680	2.379	1470		2.719
	64	0.2339	4	800	1740	2.422	1520		2.773
	66	0.2204	4	800	1720	2.593	1500		2.973
	68	0.2069	4	800	1680	2.821	1470		3.223
	70	0.1934	4	800	1710	2.957	1500		3.371
	72	0.1798	4	800	1680	3.228	1470		3.689
	74	0.1663	4	800	1690	3.462	1480		3.953
	76	0.1528	4	800	1720	3.695	1510		4.209
	78	0.1393	4	800	1670	4.167	1460		4.766
	80	0.1258	4	800	1700	4.525	1490		5.163
	82	0.1122	4	800	1710	5.033	1500		5.737
	84	0.0987	4	800	1700	5.748	1490		6.558
	86	0.0852	4	800	1710	6.612	1500		7.538
	88	0.0717	4	800	1660	8.088	1450		9.259
	90	0.0582	4	800	1710	9.667	1500		11.021
	92	0.0447	4	800	1710	12.586	1500		14.348
	94	0.0311	4	800	1680	18.364	1470		20.988
	96	0.0176	4	800	1720	31.695	1510		36.103
	98	0.0041	4	800	1720	136.376	1500		156.378
	100	-0.0094	4	800	1670	60.983	1460		69.755
1. Hanger tension taken from W.A. Fairhurst Hanger Loads Report 2. Slope calculated from historic survey see sheet 3 for calculation details.									

		Project				File location			
		Cable Band Bolt - Factor of Safety				BC04_Cable_Bands			
						Calc sheet no.	rev		
Drawing Ref		Calc by		Date	Chk by	Date			
33111/AB/20		DB		Jul2011					
Ref	Calculations					Output			
Side Span Main Span	Determine Factor of Safety Against Slip $\mu = 0.3$							HA Side Span Minimum FOS FOS = 1.764 BSALL Side Span Minimum FOS FOS = 1.942 HA Side Span Minimum FOS FOS = 1.701 Side Span Minimum FOS FOS = 1.928	
	Table 4 - Re-calculated with amended Bolt Tension								
	Panel Point	Slope	No Bolts	Bolt Tension (kN)	Dead + HA Loads + Footway (BD 37/01)	HA FOS	Dead + BSALL (2006) + Footway (BD 37/01)		BSALL FoS
	2	0.0691	4	660.00	2560	4.486	2180		5.268
	4	0.0877	4	660.00	2110	4.294	1920		4.719
	6	0.1064	4	660.00	2160	3.467	1970		3.801
	8	0.1250	4	660.00	2030	3.146	1850		3.452
	10	0.1436	4	660.00	2090	2.666	1900		2.933
	12	0.1622	4	660.00	2110	2.344	1930		2.563
	14	0.1808	4	660.00	2150	2.070	1960		2.271
	16	0.1995	4	660.00	2130	1.901	1930		2.098
	18	0.2181	6	660.00	2140	2.606	1940		2.874
	20	0.2367	6	660.00	2150	2.399	1940		2.659
	22	0.2553	6	660.00	2140	2.244	1930		2.488
	24	0.2739	6	660.00	2170	2.072	1960		2.294
	26	0.2925	6	660.00	2170	1.950	1970		2.148
	28	0.3112	6	660.00	2140	1.868	1940		2.061
	30	0.3298	6	660.00	2150	1.764	1950		1.945
	32	0.3484	8	660.00	2180	2.209	1980		2.432
	34	0.3670	8	660.00	2120	2.169	1930		2.382
	36	0.3856	8	660.00	2110	2.086	1940		2.269
	38	0.4042	8	660.00	2130	1.984	1950		2.167
	40	0.4229	8	660.00	2150	1.892	1980		2.054
	42	0.4415	8	660.00	2170	1.807	2020		1.942
	44	N/A	N/A	N/A	N/A	N/A	N/A		N/A
	46	N/A	N/A	N/A	N/A	N/A	N/A		N/A
	48	0.3421	6	629.08	1370	2.554	1310		2.671
	50	0.3286	6	693.17	1530	2.613	1390		2.876
	52	0.3150	6	725.62	1590	2.734	1420		3.061
	54	0.3015	4	658.69	1610	1.701	1420		1.928
	56	0.2880	4	717.70	1660	1.875	1460		2.131
	58	0.2745	4	699.08	1690	1.875	1480		2.141
	60	0.2610	4	666.67	1680	1.886	1470		2.155
	62	0.2474	4	673.45	1680	2.003	1470		2.289
	64	0.2339	4	693.15	1740	2.099	1520		2.402
	66	0.2204	4	666.80	1720	2.161	1500		2.478
	68	0.2069	4	692.23	1680	2.441	1470		2.789
	70	0.1934	4	660.25	1710	2.441	1500		2.782
	72	0.1798	4	666.73	1680	2.690	1470		3.075
	74	0.1663	4	679.20	1690	2.939	1480		3.356
	76	0.1528	4	647.64	1720	2.991	1510		3.407
	78	0.1393	4	626.23	1670	3.262	1460		3.731
	80	0.1258	4	635.39	1700	3.594	1490		4.101
	82	0.1122	4	650.55	1710	4.093	1500		4.666
	84	0.0987	4	595.89	1700	4.281	1490		4.884
	86	0.0852	4	732.49	1710	6.054	1500		6.902
	88	0.0717	4	695.43	1660	7.030	1450		8.049
	90	0.0582	4	602.79	1710	7.284	1500		8.304
	92	0.0447	4	657.67	1710	10.346	1500		11.795
	94	0.0311	4	643.95	1680	14.782	1470		16.894
	96	0.0176	4	624.01	1720	24.723	1510		28.161
	98	0.0041	4	638.54	1720	108.852	1500		124.817
100	-0.0094	4	625.66	1670	47.693	1460	54.553		
1. Hanger tension taken from W.A. Fairhurst Hanger Loads Report 2. Slope calculated from historic survey see sheet 3 for calculation details. 3. Tension in bolts as per FRB measurements 2007/2008.									


		Project				File location			
		Cable Band Bolt - Factor of Safety				BC04_Cable_Bands			
						Calc sheet no.	rev		
Ref		Drawing Ref		Calc by	Date	Chk by	Date		
		33111/AB/20		DB	Jul2011				
Side Span		Calculations						Output	
		Determine Factor of Safety Against Slip $\mu = 0.204$							
Main Span		Table 5 - Re-calculated with amended Bolt Tension and Reduced Slip Factor							
		Panel Point	Slope	No Bolts	Bolt Tension (kN)	Dead + HA Loads + Footway (BD 37/01)	HA FOS	Dead + BSALL (2006) + Footway (BD 37/01)	BSALL FoS
		2	0.0691	4	660.00	2560	3.050	2180	3.582
		4	0.0877	4	660.00	2110	2.920	1920	3.209
		6	0.1064	4	660.00	2160	2.357	1970	2.585
		8	0.1250	4	660.00	2030	2.139	1850	2.347
		10	0.1436	4	660.00	2090	1.813	1900	1.994
		12	0.1622	4	660.00	2110	1.594	1930	1.743
		14	0.1808	4	660.00	2150	1.408	1960	1.544
		16	0.1995	4	660.00	2130	1.293	1930	1.427
		18	0.2181	6	660.00	2140	1.772	1940	1.954
		20	0.2367	6	660.00	2150	1.631	1940	1.808
		22	0.2553	6	660.00	2140	1.526	1930	1.692
		24	0.2739	6	660.00	2170	1.409	1960	1.560
		26	0.2925	6	660.00	2170	1.326	1970	1.461
		28	0.3112	6	660.00	2140	1.271	1940	1.402
		30	0.3298	6	660.00	2150	1.200	1950	1.323
		32	0.3484	8	660.00	2180	1.502	1980	1.654
		34	0.3670	8	660.00	2120	1.475	1930	1.620
		36	0.3856	8	660.00	2110	1.419	1940	1.543
		38	0.4042	8	660.00	2130	1.349	1950	1.474
		40	0.4229	8	660.00	2150	1.286	1980	1.397
		42	0.4415	8	660.00	2170	1.229	2020	1.320
		44	N/A	N/A	N/A	N/A	N/A	N/A	N/A
		46	N/A	N/A	N/A	N/A	N/A	N/A	N/A
		48	0.3421	6	629.08	1370	1.736	1310	1.816
		50	0.3286	6	693.17	1530	1.777	1390	1.955
		52	0.3150	6	725.62	1590	1.859	1420	2.082
		54	0.3015	4	658.69	1610	1.156	1420	1.311
		56	0.2880	4	717.70	1660	1.275	1460	1.449
		58	0.2745	4	699.08	1690	1.275	1480	1.456
		60	0.2610	4	666.67	1680	1.282	1470	1.466
		62	0.2474	4	673.45	1680	1.362	1470	1.556
		64	0.2339	4	693.15	1740	1.427	1520	1.634
		66	0.2204	4	666.80	1720	1.470	1500	1.685
		68	0.2069	4	692.23	1680	1.660	1470	1.897
		70	0.1934	4	660.25	1710	1.660	1500	1.892
		72	0.1798	4	666.73	1680	1.830	1470	2.091
		74	0.1663	4	679.20	1690	1.999	1480	2.282
		76	0.1528	4	647.64	1720	2.034	1510	2.317
		78	0.1393	4	626.23	1670	2.218	1460	2.537
		80	0.1258	4	635.39	1700	2.444	1490	2.789
		82	0.1122	4	650.55	1710	2.783	1500	3.173
		84	0.0987	4	595.89	1700	2.911	1490	3.321
		86	0.0852	4	732.49	1710	4.117	1500	4.693
		88	0.0717	4	695.43	1660	4.781	1450	5.473
		90	0.0582	4	602.79	1710	4.953	1500	5.647
		92	0.0447	4	657.67	1710	7.036	1500	8.021
		94	0.0311	4	643.95	1680	10.052	1470	11.488
		96	0.0176	4	624.01	1720	16.811	1510	19.149
		98	0.0041	4	638.54	1720	74.019	1500	84.875
		100	-0.0094	4	625.66	1670	32.431	1460	37.096
		1. Hanger tension taken from W.A. Fairhurst Hanger Loads Report 2. Slope calculated from historic survey see sheet 3 for calculation details. 3. Tension in bolts as per FRB measurements 2007/2008.							
		HA Side Span Minimum FOS FOS = 1.200 BSALL Side Span Minimum FOS FOS = 1.320 HA Side Span Minimum FOS FOS = 1.156 Side Span Minimum FOS FOS = 1.311							

		Project				File location		
		Cable Band Bolt - Factor of Safety				BC04_Cable_Bands		
						Calc sheet no.	rev	
Drawing Ref		33111/AB/20		Calc by	Date	Chk by	Date	
				DB	Jul2011			
Ref	Calculations						Output	
Determine Factor of Safety Against Slip $\mu = 0.204$								
Table 5 - Re-calculated with Reduced load using Bridge Specific Footway Loading								
	Panel Point	Slope	No Bolts	Bolt Tension (kN)	Dead + HA Loads + Footway (BD37/01)	HA FOS	Dead + BSALL (2006) + Footway (BSFLL)	BSALL FoS
Side Span	2	0.0691	4	660.00	2560	3.050	2142.94	3.644
	4	0.0877	4	660.00	2110	2.920	1887.36	3.264
	6	0.1064	4	660.00	2160	2.357	1936.51	2.629
	8	0.1250	4	660.00	2030	2.139	1818.55	2.388
	10	0.1436	4	660.00	2090	1.813	1867.7	2.029
	12	0.1622	4	660.00	2110	1.594	1897.19	1.773
	14	0.1808	4	660.00	2150	1.408	1926.68	1.571
	16	0.1995	4	660.00	2130	1.293	1897.19	1.451
	18	0.2181	6	660.00	2140	1.772	1907.02	1.988
	20	0.2367	6	660.00	2150	1.631	1907.02	1.839
Main Span	22	0.2553	6	660.00	2140	1.526	1897.19	1.721
	24	0.2739	6	660.00	2170	1.409	1926.68	1.587
	26	0.2925	6	660.00	2170	1.326	1936.51	1.486
	28	0.3112	6	660.00	2140	1.271	1907.02	1.426
	30	0.3298	6	660.00	2150	1.200	1916.85	1.346
	32	0.3484	8	660.00	2180	1.502	1946.34	1.682
	34	0.3670	8	660.00	2120	1.475	1897.19	1.648
	36	0.3856	8	660.00	2110	1.419	1907.02	1.570
	38	0.4042	8	660.00	2130	1.349	1916.85	1.499
	40	0.4229	8	660.00	2150	1.286	1946.34	1.421
	42	0.4415	8	660.00	2170	1.229	1985.66	1.343
	44	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	46	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	48	0.3421	6	629.08	1370	1.736	1310	1.816
	50	0.3286	6	693.17	1530	1.777	1390	1.955
	52	0.3150	6	725.62	1590	1.859	1420	2.082
	54	0.3015	4	658.69	1610	1.156	1388.05	1.341
	56	0.2880	4	717.70	1660	1.275	1427.15	1.483
	58	0.2745	4	699.08	1690	1.275	1446.7	1.490
	60	0.2610	4	666.67	1680	1.282	1436.925	1.499
	62	0.2474	4	673.45	1680	1.362	1436.925	1.592
	64	0.2339	4	693.15	1740	1.427	1485.8	1.671
	66	0.2204	4	666.80	1720	1.470	1466.25	1.724
	68	0.2069	4	692.23	1680	1.660	1436.925	1.940
	70	0.1934	4	660.25	1710	1.660	1466.25	1.935
	72	0.1798	4	666.73	1680	1.830	1436.925	2.139
	74	0.1663	4	679.20	1690	1.999	1446.7	2.335
	76	0.1528	4	647.64	1720	2.034	1476.025	2.370
	78	0.1393	4	626.23	1670	2.218	1427.15	2.595
	80	0.1258	4	635.39	1700	2.444	1456.475	2.853
	82	0.1122	4	650.55	1710	2.783	1466.25	3.246
	84	0.0987	4	595.89	1700	2.911	1456.475	3.398
	86	0.0852	4	732.49	1710	4.117	1466.25	4.801
	88	0.0717	4	695.43	1660	4.781	1417.375	5.599
	90	0.0582	4	602.79	1710	4.953	1466.25	5.777
	92	0.0447	4	657.67	1710	7.036	1466.25	8.205
	94	0.0311	4	643.95	1680	10.052	1436.925	11.752
	96	0.0176	4	624.01	1720	16.811	1476.025	19.590
	98	0.0041	4	638.54	1720	74.019	1466.25	86.829
	100	-0.0094	4	625.66	1670	32.431	1427.15	37.950
1. Hanger tension taken from W.A. Fairhurst Hanger Loads Report 2. Slope calculated from historic survey see sheet 3 for calculation details. 3. Tension in bolts as per FRB measurements 2007/2008. 4. Bridge specific footway live loading used								
							HA Side Span Minimum FOS	FOS = 1.200
							BSALL Side Span Minimum FOS	FOS = 1.343
							HA Side Span Minimum FOS	FOS = 1.156
							Side Span Minimum FOS	FOS = 1.341


	Project			File location	
	Cable Band Bolt - Factor of Safety			BC04_Cable_Bands	
				Calc sheet no.	rev
	Drawing Ref	Calc by	Date	Chk by	Date
	33111/AB/20	DB	Jul2011		
Ref	Calculations			Output	
	<u>Discussion</u> Table 1 - Shows the calculations with input values as per WAF. Note that To achieve the same answers as MB calc, the slope has to be taken as an angle in radians. Table 2 - This Table shows the difference in slope between the calculated values using survey information and values from MB. Table shows that survey corresponds to the slope as stated on MB calculations. It can therefore seen that slope should not be assumed to be angle in radians. Table 3 - Calculations were undertaken using specific hanger loads as stated from WAF hanger loads report. Only marginal changes were noted between assumed loading and calculated loading for hangers. In addition calculations were undertaken to show the theoretical FOS if HA loading was applied instead of the bridge specific loading. As suspected this reduced the FOS of the hangers however the FOS for these calculated hanger are still above the required FOS. Table 4 - Calculations were undertaken using the re-measured tension in the cable band bolts. This significantly reduced the FOS to 1.9424 for the side span and 1.928 for the MS. This is below the required FOS as calculated previously for a ym of 1.67 however above the FOS if ym of 1.30 is assumed assumed. Table 5 - Shows the FOS achieved if a reduced slip factor is used. Results show that for the majority of hanger locations the cable band bolts do not have a sufficient FOS. Table 6 - This table shows the FOS as calculated in table 5 with a reduced hanger load calculated by substituting BD37/01 footway live load for the bridge specific footway live loading. Note that the reduction in load is minimal due to the large loaded length.				

	<u>Project</u> Cable Band Bolt - Factor of Safety			<u>File location</u> BC04_Cable_Bands	
				<u>Calc sheet no.</u>	<u>rev</u>
	<u>Drawing Ref</u> 33111/AB/20	<u>Calc by</u> DB	<u>Date</u> Jul2011	<u>Chk by</u>	<u>Date</u>
Ref	Calculations			Output	
	<u>Appendix A</u>				


Main Cable Survey




West Main Span Cable



Main Cable Side Span South



Main Cable Side Span North



Survey of Main cable and Deck - West Side

Point	Date	Level	Northing
200	840520	46.546	1588.044
201	840520	40.802	1572.096 cable
202	840520	35.158	1556.311 S Back Stay
203	840520	29.544	1540.472
204	840520	23.981	1524.632
205	840520	18.45	1508.781
206	840520	12.959	1492.898
230	840520	48.531	1597.505
231	840520	49.937	1615.1
232	840520	51.698	1633.215
233	840520	53.772	1651.336
234	840520	56.175	1669.45
235	840520	58.892	1687.569
236	840520	61.916	1705.692
237	840520	65.288	1723.811
238	840520	68.966	1741.929
239	840520	72.926	1760.061 cable
240	840520	77.261	1778.17 S side Span
241	840520	81.907	1796.282
242	840520	86.854	1814.416
243	840520	92.14	1832.545
244	840520	97.793	1850.65
245	840520	103.677	1868.803
246	840520	109.981	1886.916
247	840520	116.56	1905.041
248	840520	123.501	1923.197
249	840520	130.738	1941.29
250	840520	138.326	1959.423
251	840520	146.238	1977.55
252	840520	153.601	1993.713
260	840520	66.012	2493.958
261	840520	66.245	2475.825
262	840520	66.694	2457.704
263	840520	67.376	2439.57
264	840520	68.333	2421.463
265	840520	69.449	2403.325
266	840520	70.9	2385.222
267	840520	72.542	2367.095
268	840520	74.375	2348.964
269	840520	76.475	2330.842
270	840520	78.795	2312.718
271	840520	81.419	2294.604 cable
272	840520	84.277	2276.49 S half Main Span
273	840520	87.235	2258.338
274	840520	90.529	2240.212
275	840520	94.057	2222.088
276	840520	97.83	2203.961
277	840520	101.84	2185.835
278	840520	106.06	2167.706

South Tower Northing =
North Tower Northing =

279	840520	110.524	2149.57
280	840520	115.229	2131.423
281	840520	120.186	2113.296
282	840520	125.372	2095.177
283	840520	130.781	2077.029
284	840520	136.428	2058.881
285	840520	142.341	2040.756
286	840520	148.48	2022.633
287	840520	154.19	2006.408

400	840617	13.02	3512.679
401	840617	18.516	3496.775
402	840617	24.038	3480.969 cable
403	840617	29.59	3465.189 N back Stay
404	840617	35.191	3449.397
405	840617	40.817	3433.643
406	840617	46.58	3417.768

431	840617	65.659	2511.996
432	840617	65.924	2530.107
433	840617	66.375	2548.238
434	840617	67.088	2566.351
435	840617	68.02	2584.476
436	840617	69.207	2602.598
437	840617	70.644	2620.718
438	840617	72.26	2638.846
439	840617	74.138	2656.965
440	840617	76.237	2675.095
441	840617	78.573	2693.217 cable
442	840617	81.198	2711.334 N side span
443	840617	84.005	2729.466
444	840617	87.074	2747.598
445	840617	90.366	2765.723
446	840617	93.904	2783.842
447	840617	97.665	2801.978
448	840617	101.683	2820.106
449	840617	105.938	2838.244
450	840617	110.421	2856.364
451	840617	115.151	2874.495
452	840617	120.127	2892.621
453	840617	125.325	2910.752
454	840617	130.759	2928.887
455	840617	136.446	2947.026
456	840617	142.367	2965.155
457	840617	148.512	2983.273
458	840617	154.251	2999.504
459	840617	153.657	3012.111
460	840617	146.302	3028.252
461	840617	138.336	3046.37
462	840617	130.764	3064.487
463	840617	123.497	3082.611
464	840617	116.566	3100.746
465	840617	109.948	3118.853
466	840617	103.656	3136.978
467	840617	97.719	3155.116

468	840617	92.073	3173.228	cable
469	840617	86.78	3191.36	N half of Main span
470	840617	81.811	3209.488	
471	840617	77.131	3227.613	
472	840617	72.829	3245.736	
473	840617	68.831	3263.86	
474	840617	65.148	3281.991	
475	840617	61.794	3300.108	
476	840617	58.771	3318.257	
477	840617	56.058	3336.361	
478	840617	53.708	3354.501	
479	840617	51.667	3372.622	
480	840617	49.953	3390.745	
481	840617	48.578	3408.331	

deck S side Span



2006.408
2999.514

Main Cable Transposed Values Main Span					
Point	Date	Level			Northing Chainage
260	840520	66.012	2493.958	487.550	
261	840520	66.245	2475.825	469.417	
262	840520	66.694	2457.704	451.296	
263	840520	67.376	2439.57	433.162	
264	840520	68.333	2421.463	415.055	
265	840520	69.449	2403.325	396.917	
266	840520	70.9	2385.222	378.814	
267	840520	72.542	2367.095	360.687	
268	840520	74.375	2348.964	342.556	
269	840520	76.475	2330.842	324.434	
270	840520	78.795	2312.718	306.310	
271	840520	81.419	2294.604	288.196	
272	840520	84.277	2276.49	270.082	
273	840520	87.235	2258.338	251.930	
274	840520	90.529	2240.212	233.804	
275	840520	94.057	2222.088	215.680	
276	840520	97.83	2203.961	197.553	
277	840520	101.84	2185.835	179.427	
278	840520	106.06	2167.706	161.298	
279	840520	110.524	2149.57	143.162	
280	840520	115.229	2131.423	125.015	
281	840520	120.186	2113.296	106.888	
282	840520	125.372	2095.177	88.769	

Main Cable Point

283	840520	130.781	2077.029	70.621
284	840520	136.428	2058.881	52.473
285	840520	142.341	2040.756	34.348
286	840520	148.48	2022.633	16.225
287	840520	154.19	2006.408	0.000

Main Cable
Point

230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252

252		153.601	1993.713	0
251		146.238	1977.55	16.163
250		138.326	1959.423	34.29

249		130.738	1941.29	52.423
248		123.501	1923.167	70.546
247		116.56	1905.041	88.672
246		109.981	1886.916	106.797
245		103.677	1868.803	124.91
244		97.793	1850.65	143.063
243		92.14	1832.545	161.168
242		86.854	1814.416	179.297
241		81.907	1796.282	197.431
240		77.261	1778.17	215.543
239		72.926	1760.061	233.652
238		68.966	1741.929	251.784
237		65.288	1723.811	269.902
236		61.916	1705.692	288.021
235		58.892	1687.569	306.144
234		56.175	1669.45	324.263
233		53.772	1651.336	342.377
232		51.698	1633.215	360.498
231		49.937	1615.1	378.613
230		48.531	1597.505	396.208

Transposed Values North Side Span			
Date	Level	Northing	Chainage
	48.531	1597.505	0
	49.937	1615.1	17.595
	51.698	1633.215	35.71
	53.772	1651.336	53.831
	56.175	1669.45	71.945
	58.892	1687.569	90.064
	61.916	1705.692	108.187
	65.288	1723.811	126.306
	68.966	1741.929	144.424
	72.926	1760.061	162.556
	77.261	1778.17	180.665
	81.907	1796.282	198.777
	86.854	1814.416	216.911
	92.14	1832.545	235.04
	97.793	1850.65	253.145
	103.677	1868.803	271.298
	109.981	1886.916	289.411
	116.56	1905.041	307.536
	123.501	1923.167	325.662
	130.738	1941.29	343.785
	138.326	1959.423	361.918
	146.238	1977.55	380.045
	153.601	1993.713	396.208

4

Height (m)

160

140

120

100



80


60

40



20

0







0.000





many cable and optical fiber




Main Cable Side Span North





Main Cable Survey







h





◆ South Side Span
— Poly. (South Side Span)





Survey of Main cable and Deck - West Side

Point	Date	Level	Northing
10	840520	46.538	1588.048
11	840520	40.833	1572.077 cable
12	840520	35.15	1556.322 S Back Stay
13	840520	29.543	1540.496
14	840520	23.974	1524.642
15	840520	18.457	1508.794
31	840520	50.071	1615.068
32	840520	51.791	1633.184
33	840520	53.834	1651.32
35	840520	56.267	1669.422
36	840520	58.901	1687.569
37	840520	61.937	1705.69
38	840520	65.351	1723.791
39	840520	68.969	1741.932
40	840520	72.967	1760.065
41	840520	77.402	1778.138 cable
42	840520	82.032	1796.269 S side Span
43	840520	86.963	1814.396
44	840520	92.235	1832.527
45	840520	97.779	1850.673
46	840520	103.708	1868.806
47	840520	109.969	1886.939
48	840520	116.578	1905.06
49	840520	123.501	1923.197
50	840520	130.75	1941.323
51	840520	138.336	1959.45
52	840520	146.251	1977.574
53	840520	153.6	1993.714
70	840520	65.967	2493.859
71	840520	66.179	2475.739
72	840520	66.663	2457.62
73	840520	67.339	2439.504
74	840520	68.303	2421.39
75	840520	69.468	2403.265
76	840520	70.854	2385.143
77	840520	72.493	2367.017
78	840520	74.369	2348.894
79	840520	76.435	2330.755
80	840520	78.825	2312.649
81	840520	81.405	2294.526 cable
82	840520	84.186	2276.387 S half Main Span
83	840520	87.242	2258.261
84	840520	90.501	2240.137
85	840520	94.045	2222.006
86	840520	97.82	2203.882
87	840520	101.83	2185.762
88	840520	106.043	2167.63
89	840520	110.502	2149.497
90	840520	115.218	2131.353
91	840520	120.174	2113.234

South Tower Northing =
North Tower Northing =

92	840520	125.358	2095.089
93	840520	130.776	2076.947
94	840520	136.439	2058.811
95	840520	142.349	2040.679
96	840520	148.486	2022.54
97	840520	154.204	2006.305

300	840715	46.569	3417.774
301	840715	40.79	3433.734
302	840715	35.171	3449.477 cable
303	840715	29.559	3465.246 N back Stay
304	840715	24.011	3481.029
305	840715	18.504	3496.832
306	840715	13.022	3512.788

330	840715	48.566	3408.3
331	840715	49.968	3390.73
332	840715	51.701	3372.613
333	840715	53.747	3354.482
334	840715	56.123	3336.375
335	840715	58.83	3318.264
336	840715	61.816	3300.099
337	840715	65.195	3281.997
338	840715	68.919	3263.9
339	840715	72.961	3245.772
340	840715	77.25	3227.652 cable
341	840715	81.811	3209.5 N side span
342	840715	86.804	3191.374
343	840715	92.121	3173.261
344	840715	97.762	3155.145
345	840715	103.711	3137.018
346	840715	109.98	3118.87
347	840715	116.591	3100.763
348	840715	123.531	3082.634
349	840715	130.789	3064.509
350	840715	138.374	3046.383
351	840715	146.315	3028.234
352	840715	153.646	3012.14

362	840715	65.828	2511.975
363	840715	66.097	2530.099
364	840715	66.584	2548.219
365	840715	67.294	2566.333
366	840715	68.197	2584.461
367	840715	69.394	2602.585
368	840715	70.804	2620.7
369	840715	72.403	2638.832
370	840715	74.349	2656.951
371	840715	76.42	2675.089
372	840715	78.749	2693.209
373	840715	81.342	2711.328
374	840715	84.157	2729.452
375	840715	87.253	2747.568 cable
376	840715	90.531	2765.7 N half of Main span
377	840715	94.044	2783.833
378	840715	97.817	2801.966

379	840715	101.837	2820.095
380	840715	106.053	2838.237
381	840715	110.528	2856.365
382	840715	115.256	2874.503
383	840715	120.206	2892.627
384	840715	125.398	2910.747
385	840715	130.819	2928.88
386	840715	136.484	2947.022
387	840715	142.384	2965.151
388	840715	148.515	2983.279
389	840715	154.234	2999.514

1000	840715
1001	840715
1002	840715
1003	840715
1004	840715
1005	840715
1006	840715
1007	840715
1008	840715
1009	840715
1010	840715
1011	840715
1012	840715
1013	840715
1014	840715
1015	840715
1016	840715
1017	840715
1018	840715
1019	840715
1020	840715
1021	840715

deck S side Span

1022	840715	58.156
1023	840715	58.479
1024	840715	58.79
1025	840715	59.098
1026	840715	59.398
1027	840715	59.676
1028	840715	59.966
1029	840715	60.237
1030	840715	60.507
1031	840715	60.749
1032	840715	61.003
1033	840715	61.231
1034	840715	61.447
1035	840715	61.647
1036	840715	61.843
1037	840715	62.03
1038	840715	62.19
1039	840715	62.323
1040	840715	62.473
1041	840715	62.597
1042	840715	62.703

1043	840715	62.799
1044	840715	62.883
1045	840715	62.963
1046	840715	62.975
1047	840715	63.041
1048	840715	63.063
1049	840715	63.064
1050	840715	63.053
1051	840715	63.053
1052	840715	63.044
1053	840715	62.997
1054	840715	62.959
1055	840715	62.892
1056	840715	62.82
1057	840715	62.707
1058	840715	62.592
1059	840715	62.494
1060	840715	62.36
1061	840715	62.194
1062	840715	62.018
1063	840715	61.84
1064	840715	61.639
1065	840715	61.428
1066	840715	61.217
1067	840715	60.975
1068	840715	60.713
1069	840715	60.44
1070	840715	60.18
1071	840715	59.891
1072	840715	59.574
1073	840715	59.259
1074	840715	58.931
1075	840715	58.583
1076	840715	58.214
1077	840715	58.214

[illegible]

[illegible]

2006.305
2999.514

Main Cable Transposed Values Main Span					
Point	Date	Level		Northing	Chainage
97.000	840520.000	154.204	154.204	2006.305	0.000
96.000	840520.000	148.486	148.486	2022.540	16.235
95.000	840520.000	142.349	142.349	2040.679	34.374
94.000	840520.000	136.439	136.439	2058.811	52.506
93.000	840520.000	130.776	130.776	2076.947	70.642
92.000	840520.000	125.358	125.358	2095.089	88.784
91.000	840520.000	120.174	120.174	2113.234	106.929
90.000	840520.000	115.218	115.218	2131.353	125.048
89.000	840520.000	110.502	110.502	2149.497	143.192
88.000	840520.000	106.043	106.043	2167.630	161.325
87.000	840520.000	101.830	101.830	2185.762	179.457
86.000	840520.000	97.820	97.820	2203.882	197.577
85.000	840520.000	94.045	94.045	2222.006	215.701
84.000	840520.000	90.501	90.501	2240.137	233.832
83.000	840520.000	87.242	87.242	2258.261	251.956
82.000	840520.000	84.186	84.186	2276.387	270.082
81.000	840520.000	81.405	81.405	2294.526	288.221
80.000	840520.000	78.825	78.825	2312.649	306.344
79.000	840520.000	76.435	76.435	2330.755	324.450
78.000	840520.000	74.369	74.369	2348.894	342.589
77.000	840520.000	72.493	72.493	2367.017	360.712
76.000	840520.000	70.854	70.854	2385.143	378.838
75.000	840520.000	69.468	69.468	2403.265	396.960
74.000	840520.000	68.303	68.303	2421.390	415.085
73.000	840520.000	67.339	67.339	2439.504	433.199
72.000	840520.000	66.663	66.663	2457.620	451.315

Main Cable Point
31
32
33
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53

Main Cable Point

71.000	840520.000	66.179	66.179	2475.739	469.434
70.000	840520.000	65.967	65.967	2493.859	487.554
362.000	840715.000	65.828	65.828	2511.975	505.670
363.000	840715.000	66.097	66.097	2530.099	523.794
364.000	840715.000	66.584	66.584	2548.219	541.914
365.000	840715.000	67.294	67.294	2566.333	560.028
366.000	840715.000	68.197	68.197	2584.461	578.156
367.000	840715.000	69.394	69.394	2602.585	596.280
368.000	840715.000	70.804	70.804	2620.700	614.395
369.000	840715.000	72.403	72.403	2638.832	632.527
370.000	840715.000	74.349	74.349	2656.951	650.646
371.000	840715.000	76.420	76.420	2675.089	668.784
372.000	840715.000	78.749	78.749	2693.209	686.904
373.000	840715.000	81.342	81.342	2711.328	705.023
374.000	840715.000	84.157	84.157	2729.452	723.147
375.000	840715.000	87.253	87.253	2747.568	741.263
376.000	840715.000	90.531	90.531	2765.700	759.395
377.000	840715.000	94.044	94.044	2783.833	777.528
378.000	840715.000	97.817	97.817	2801.966	795.661
379.000	840715.000	101.837	101.837	2820.095	813.790
380.000	840715.000	106.053	106.053	2838.237	831.932
381.000	840715.000	110.528	110.528	2856.365	850.060
382.000	840715.000	115.256	115.256	2874.503	868.198
383.000	840715.000	120.206	120.206	2892.627	886.322
384.000	840715.000	125.398	125.398	2910.747	904.442
385.000	840715.000	130.819	130.819	2928.880	922.575
386.000	840715.000	136.484	136.484	2947.022	940.717
387.000	840715.000	142.384	142.384	2965.151	958.846
388.000	840715.000	148.515	148.515	2983.279	976.974
389.000	840715.000	154.234	154.234	2999.514	993.209

352
351
350
349
348
347
346
345
344
343
342
341
340
339
338
337
336
335
334
333
332
331
330

: Transposed Values South Side Span			
Date	Level	Northing	Chainage
840520	50.071	1615.068	0
840520	51.791	1633.184	18.116
840520	53.834	1651.32	36.252
840520	56.267	1669.422	54.354
840520	58.901	1687.569	72.501
840520	61.937	1705.69	90.622
840520	65.351	1723.791	108.723
840520	68.969	1741.932	126.864
840520	72.967	1760.065	144.997
840520	77.402	1778.138	163.07
840520	82.032	1796.269	181.201
840520	86.963	1814.396	199.328
840520	92.235	1832.527	217.459
840520	97.779	1850.673	235.605
840520	103.708	1868.806	253.738
840520	109.969	1886.939	271.871
840520	116.578	1905.06	289.992
840520	123.501	1923.197	308.129
840520	130.75	1941.323	326.255
840520	138.336	1959.45	344.382
840520	146.251	1977.574	362.506
840520	153.6	1993.714	378.646

: Transposed Values North Side Span			
Date	Level	Northing	Chainage

840715	153.646	3012.14	0
840715	146.315	3028.234	16.094
840715	138.374	3046.383	34.243
840715	130.789	3064.509	52.369
840715	123.531	3082.634	70.494
840715	116.591	3100.763	88.623
840715	109.98	3118.87	106.73
840715	103.711	3137.018	124.878
840715	97.762	3155.145	143.005
840715	92.121	3173.261	161.121
840715	86.804	3191.374	179.234
840715	81.811	3209.5	197.36
840715	77.25	3227.652	215.512
840715	72.961	3245.772	233.632
840715	68.919	3263.9	251.76
840715	65.195	3281.997	269.857
840715	61.816	3300.099	287.959
840715	58.83	3318.264	306.124
840715	56.123	3336.375	324.235
840715	53.747	3354.482	342.342
840715	51.701	3372.613	360.473
840715	49.968	3390.73	378.59
840715	48.566	3408.3	396.16

444.875
0

Appendix B

Nominal axial loads in the hangers

	PP			
		Dead Load	Superimposed Dead Load	HA Loads + Footway (BD 37/01)
Side Span	2	1.31	0.33	0.92
	4	1.29	0.28	0.54
	6	1.32	0.29	0.55
	8	1.23	0.27	0.53
	10	1.27	0.28	0.54
	12	1.28	0.28	0.55
	14	1.3	0.28	0.57
	16	1.28	0.27	0.58
	18	1.27	0.27	0.6
	20	1.28	0.27	0.6
	22	1.27	0.27	0.6
	24	1.3	0.27	0.6
	26	1.3	0.27	0.6
	28	1.27	0.27	0.6
	30	1.28	0.27	0.6
	32	1.31	0.28	0.59
	34	1.27	0.28	0.57
	36	1.29	0.28	0.54
	38	1.31	0.29	0.53
	40	1.37	0.28	0.5
	42	1.52	0.24	0.41

Table 2 - Hanger Loads - Side Span

	PP			
		Dead Load	Superimposed Dead Load	HA Loads + Footway (BD 37/01)
	48	1.11	0.1	0.16
	50	0.92	0.22	0.39
	52	0.85	0.26	0.48
	54	0.81	0.27	0.53
	56	0.83	0.27	0.56
	58	0.84	0.27	0.58
	60	0.81	0.27	0.6
	62	0.81	0.27	0.6
	64	0.84	0.28	0.62
	66	0.83	0.27	0.62

Side Span	68	0.81	0.27	0.6
	70	0.84	0.27	0.6
	72	0.81	0.27	0.6
	74	0.83	0.27	0.59
	76	0.85	0.27	0.6
	78	0.8	0.27	0.6
	80	0.83	0.27	0.6
	82	0.83	0.27	0.61
	84	0.83	0.27	0.6
	86	0.83	0.27	0.61
	88	0.79	0.27	0.6
	90	0.83	0.27	0.61
	92	0.83	0.27	0.61
	94	0.79	0.27	0.62
	96	0.83	0.27	0.62
	98	0.83	0.27	0.62
	100	0.79	0.27	0.61

Table 3- Hanger Loads - Main Span

Nominal Axial load in the hangers - Fx (MN)

BSALL (2006) + Footway (BD 37/01)	Dead + Superimposed + HA Loads + Footway (BD 37/01)	Dead + Superimposed + BSALL (2006) + Footway (BD 37/01)
0.54	2.56	2.18
0.35	2.11	1.92
0.36	2.16	1.97
0.35	2.03	1.85
0.35	2.09	1.9
0.37	2.11	1.93
0.38	2.15	1.96
0.38	2.13	1.93
0.4	2.14	1.94
0.39	2.15	1.94
0.39	2.14	1.93
0.39	2.17	1.96
0.4	2.17	1.97
0.4	2.14	1.94
0.4	2.15	1.95
0.39	2.18	1.98
0.38	2.12	1.93
0.37	2.11	1.94
0.35	2.13	1.95
0.33	2.15	1.98
0.26	2.17	2.02

Nominal Axial load in the hangers - Fx (MN)

BSALL (2006) + Footway (BD 37/01)	Dead + Superimposed + HA Loads + Footway (BD 37/01)	Dead + Superimposed + BSALL (2006) + Footway (BD 37/01)
0.1	1.37	1.31
0.25	1.53	1.39
0.31	1.59	1.42
0.34	1.61	1.42
0.36	1.66	1.46
0.37	1.69	1.48
0.39	1.68	1.47
0.39	1.68	1.47
0.4	1.74	1.52
0.4	1.72	1.5

0.39	1.68	1.47
0.39	1.71	1.5
0.39	1.68	1.47
0.38	1.69	1.48
0.39	1.72	1.51
0.39	1.67	1.46
0.39	1.7	1.49
0.4	1.71	1.5
0.390	1.7	1.49
0.400	1.71	1.5
0.390	1.66	1.45
0.400	1.71	1.5
0.400	1.71	1.5
0.410	1.68	1.47
0.410	1.72	1.51
0.400	1.72	1.5
0.400	1.67	1.460

1.47037037

1.955714