

**MAIN CABLE HANDSTRAND CLAMP
INSPECTION
PANEL POINT 16 NORTH EAST**

Original Dimensions	West Arrangement	East Arrangement
Galvanised Washer O.D. 44mm Dia. I.D. 21mm Dia.	O.D. 45.5mm I.D. 21mm	O.D. 45.66mm I.D. 20.84
Clamp Hole Dia. 21mm +0.00mm -0.5mm Width 25mm	Hole Dia. 21.13mm Width 25.01 mm	Hole Dia. 21.13mm Width 25.70mm
Bronze Washer O.D. 42mm Dia. I.D. 21mm Dia. Thickness 3mm +0.00mm -0.1mm	O.D. 42.19mm I.D. 20.92mm Thickness 3mm	O.D. 42.29mm I.D. 20.96mm Thickness 2.09mm
Bronze Sleeve O.D. 31mm Dia. +0.00mm -0.2mm I.D. 20.5mm Dia. +0.00mm -0.3mm Length 42mm +0.00mm -0.5mm	O.D. 31mm I.D. 20.17mm Length 42mm	(NYLON SLEEVE) O.D. 30.2mm I.D. 21.73mm Length 42mm
Casting I.D. 31mm Dia. Width 42mm	I.D. 31.1mm Width 42.34mm	I.D. 30.41mm Width 43mm
Bronze Washer O.D. 42mm Dia. I.D. 21mm Dia. Thickness 3mm +0.00mm -0.1mm	O.D. 42.32mm I.D. 20.81mm Thickness 2.40mm	O.D. 42.19mm I.D. 20.86mm Thickness 2.98mm
Clamp Hole Dia. 21mm +0.00mm -0.5mm Width 25mm	Hole Dia. 21.29mm Width 25.16mm	Hole Dia. 20.91mm Width 25.37mm
Galvanised Washer O.D. 44mm Dia. I.D. 21mm Dia.	O.D. 45.47mm I.D. 21.05mm	O.D. 45.36mm I.D. 20.93mm
Dim. Between Clamps	49.8mm(NTH SIDE) 50.07mm(STH SIDE)	49.41mm(NTH SIDE) 49.18mm(STH SIDE)
Bolt M20 X 100(shoulder) X 35 (thread) (8.8)		